

## Thermography



IP  
65

### C.A 1879, thermographic camera

#### > Energy loss diagnostics

- Large LCD screen & removable handle
- Mixing of real and infrared images with Merge function
- Visual and audio alarms
- Automatic detection of Max / Min temperature points
- Storage on SD card
- Voice comments

#### ■ C.A 1879

#### Specifications

Detector	47 x 47, refresh rate 8 Hz
Optical specifications	Field of view: 20° x 20° Min. focal distance: 50 cm
Measurement range	-10 °C to +350 °C, ±2% or ±2 °C
Adjustment	Emissivity, reflected temperature
Memory	1,000 images on SD card
Functions	Merge: real / infrared image mix level, adjustable by the user Voice and/or text comments
Measurement tools	2 movable cursors, automatic Min / Max temp. detection, alarm, isotherm, profile
Ergonomics	Battery life: 6 hours Removable handle, < 700 g

### State at delivery

- > The cameras are delivered in a hard case with 1 handle, 1 mains adapter for charging, 1 USB cable, 1 operating manual, software on CD-ROM, 1 quick start-up guide on paper

### Accessories/Replacement parts

USB cable  
In-vehicle adapter

> Contact us  
> HX0061

### Reference to order

> DiaCAM C.A 1879

> P01651250

